



OMNIAIRE 2000C

HEPA Air Filtration Machine

ORDERING INFO

| | |
|--|----------------|
| OmniAire 2000C | OA2000C |
| Primary/Secondary Two-Stage Filters (box of 20) | OFP2518 |
| HEPA Filter 99.97%, 0.3u (pb frame) | OAH2418 |
| HEPA Filter 99.99%, 0.3u (metal frame) | OAH2418G |
| HEPA Filter 99.97%, 0.3u (pb frame, high capacity) | OAH2418-PB-HC |
| Bag Filter Housing (includes 1 Bag Filter) | HBF2000 |
| Bag Filter MERV 15 | OBF9 |
| Vapor Trap V-bank Filter | OCVT18 |
| OdorGuard 600 Carbon Filter | OG2418D |
| Intake Manifold Kit (Manifold, Clamp & 3' Duct) | OAIM2000-12KIT |
| ABS Plastic Intake Manifold, 12" Dia. | OAIM2000-12 |
| Quick Clamp, 12"-16" Dia. | QCW14 |
| Flexible Duct, 12" Dia. x 25' L | OAD12 |
| Flexible Duct, Wire & Fiber Reinforced | OAD12R |

PART NUMBER



UL 507:1997/R:2017-01
CAN/CSA-C22.2 No. 113-15

The OmniAire 2000C is a construction grade HEPA air scrubber, delivering the performance of a full sized negative air unit but is compact and easy to move and set up. The 2000C is used to create positive or negative pressure at asbestos, lead and mold abatement projects, for collection of construction dust from cutting or grinding of concrete, wood or plaster. The HEPA filter can also be replaced with an economical multi-pocket bag filter. Additional accessories include intake manifold, flex ducting and quick clamps.

OmniAire 2000C

| | |
|---------------------------|--|
| Airflow* | 1900 CFM |
| Power Requirements | 115VAC/60 Hz/10.6 Amp |
| Motor | 1 HP with thermal overload |
| Controls | speed switch - HIGH/OFF/LOW; amber change filter indicator light; red power indicator light |
| Filtration | HEPA filter 99.97% @ 0.3μ; MERV 9 primary/secondary filter Optional: MERV 15 bag filter; OdorGuard 600 activated carbon web filter; VaporTrap V-bank filter (27 lbs of active carbon); HEPA filter 99.99% @ 0.3μ |
| Housing | galvanized metal; silicone sealed before riveting; 12" outlet; (4) rubber grip handles; (2) 5" hospital grade locking casters; (2) 5" rigid casters |
| Size/Weight | 20"W x 32"H x 34"L; 135 lbs. |

*Maximum airflow specifications based on published performance specifications of key system components including a premium, unused HEPA filter. Field results may vary.