

## **EMNIAIRE 2000V**HEPA Air Filtration Machine

ORDERING INFO	PART NUMBER
OmniAire 2000V	OA2000V
Primary/Secondary Two-Stage Filters (box of 2	OFP2518
HEPA Filter 99.97%, 0.3u (pb frame)	OAH2418
HEPA Filter 99.99%, 0.3u (metal frame)	OAH2418G
HEPA Filter 99.97%, 0.3 u  (pb frame, high capacity)	OAH2418-PB-HC
Bag Filter Housing (includes 1 Bag Filter)	HBF2000
Bag Filter MERV 15	OBF9
Vapor Trap V-bank Filter	OCVT18
OdorGuard 600 Carbon Filter	OG2418D
Intake Manifold Kit (Manifold, Clamp & 3' Duct)	OAIM2000-12KIT
ABS Plastic Intake Manifold, 12" Dia.	OAIM2000-12
Quick Clamp, 12"-16" Dia.	QCW14
Flexible Duct, 12" Dia. x 25' L	OAD12
Flexible Duct. Wire & Fiber Reinforced	OAD12R





The OmniAire 2000V is a compact and versatile, variable speed HEPA air filtration machine/air scrubber that delivers the performance of full size negative air machines. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. Designed and built with multiple filter options including HEPA, 8-Pocket Bag filter for construction dust, and activated carbon filters to meet your job requirements. Additional accessories include intake manifold, flex ducting and quick clamps.

	OmniAire 2000 V
Airflow <sup>*</sup>	1900 CFM
Power Requirements	115VAC/60 Hz/10.6 Amp
Motor	1.25 HP with thermal overload
Controls	speed switch - HIGH/OFF/Speed Control; variable speed controller; amber change filter indicator light; red power indicator light
Filtration	HEPA filter 99.97% @ 0.3µ; MERV 9 primary/secondary filter Optional: MERV 15 bag filter; OdorGuard 600 activated carbon web filter; VaporTrap V-bank filter (27 lbs of active carbon); HEPA filter 99.99% @ 0.3µ
Housing	aircraft grade aluminum; silicone sealed before riveting; 12" outlet; (4) rubber grip handles; (2) 5" hospital grade locking casters; (2) 5" rigid casters
Size/Weight	20"W x 32"H x 34"L; 117 lbs.



\*Maximum airflow specifications based on published performance specifications of key system

components including a premium, unused HEPA filter. Field results may vary.