

OMNI IQ™ G700 SERIES

INTELLIGENT DIFFERENTIAL PRESSURE MONITORING



OVERVIEW

The Omni IQ™ G700 Series delivers reliable, ICRA 2.0-compliant differential pressure monitoring for healthcare construction, abatement, and other critical environments.

Designed for real-world job sites, the G700 Series provides instant visibility into room conditions, automates compliance reporting, and supports flexible deployment options.

AT A GLANCE

- **ICRA 2.0 Compliance** – Meet and exceed infection control requirements
- **Instant Alert** – Receive alarms via the device, online portal, email, and SMS
- **Automated Reporting** – Generate and export compliance reports instantly
- **Never Miss An Alert** – Wi-Fi + Cellular with smart alert escalation so no alert is ever missed
- **FlexGo™ Mounting** – A universal mounting system that works with any containment
- **Industry-Leading Accuracy** - More precise than other portable pressure monitoring devices

APPLICATIONS



Healthcare construction & renovation



Infection control in occupied facilities



Temporary containment



Abatement & remediation projects



Critical room pressure monitoring



Mobile HEPA cart integration

KEY FEATURES & BENEFITS

Enjoy Complimentary First-Year Software

Get full access to premium Omni IQ™ features right out of the box — including remote device control, shareable projects, predictive alerts, unlimited data retention, and more.

Instant Alerts with Auto Escalation

Audible, visual, and digital notifications ensure no drop goes unnoticed, while customizable escalation paths get the right person involved immediately.

Mount Anywhere with Long-Lasting Power

FlexGo™ universal mounting adapts to any containment type, paired with weeks of battery life for hassle-free deployment on short or extended projects.

Centralized Visibility & Anytime Access

Dashboard and mobile app provide real-time oversight across all jobsites, with the ability to download and share reports anytime, anywhere — ensuring you're always ready for audits, inspections, or client updates.

TriZone™ Monitoring (G720) & Free Cellular Plan

Tracks 2 zones plus a reference point—covering construction, anteroom, and corridor. Both models include built-in cellular and Wi-Fi for continuous monitoring, reporting, and alerts.

Industry-Leading Accuracy in a Portable Monitor

Delivers more precise pressure readings than comparable portable devices, giving project teams and hospitals confidence that compliance data is precise and audit-ready.

SPECIFICATIONS


| | G700 | G720 |
|-----------------------------------|--|--|
| Performance | | |
| Operating Pressure Range | | +/- 0.10 in. W.C.* |
| Accuracy | | +/- 0.0007 in. W.C. |
| Monitor Zones | 2 | 3 |
| Hysteresis | | .05% of selected range (0.05 * 0.2 in. W.C.) |
| Non-repeatability | | .025% of range (0.025 * 0.2 in. W.C.) |
| Long-term Stability | | +/- 0.005 in. W.C. per year |
| Overpressure | | 120 in. W.C. |
| Pressure Media | | Air or non-conductive, non-explosive gases |
| Pressure Fittings | 2x Pressure port for tubing with 1/8" inner diameter | 3x Pressure port for tubing with 1/8" inner diameter |
| Display | | |
| Touch Screen Display | | 5" |
| Resolution | | 0.0001 in. W.C. |
| Power | | |
| Power | | 24VDC (Adapter provided) |
| Rechargeable Battery Life | Up to 15 days | Up to 15 days |
| Connectivity & Storage | | |
| Wi-Fi | | Yes |
| Cellular | | Yes (5-year included) |
| Local Data Storage | 32 GB | 64 GB |
| Environmental | | |
| Operating Temp | | 32°F to 104°F (0°C to +40°C) |
| Storage Temp | | 4°F to 140°F (-20°C to +60°C) |
| Humidity | | 10% to 90% RH**, non-condensing |
| Physical Description | | |
| Dimensions (Inner Enclosure) | | 8.2" x 5.6" x 2.2" (208x143x55mm) |
| Dimensions (Outer Enclosure) | | 12.4" x 10.4" x 5.3" (314x265x134mm) |
| Weight | 8 lbs | 8.2 lbs |
| Side LED Indicator | | Green, Red, Off |
| Audible Alarm | | 90 dB |
| USB Port | | USB-A Data Only |
| Regulatory Compliance | | |
| FCC | | Part 15.107 Class A |
| ISED Canada | | ICES-003 Class A |

*in. W.C. = inches of water column (unit of differential pressure)


**RH = relative humidity (non-condensing)

DIMENSIONS


OUTER ENCLOSURE



FRONT VIEW




TOP VIEW




SIDE VIEW


INNER ENCLOSURE



FRONT VIEW



TOP VIEW



SIDE VIEW

ORDERING INFORMATION

| Model Number | Description |
|----------------|--|
| IQ-G700 | Intelligent Differential Pressure Monitor – Basic |
| IQ-G720 | Intelligent Differential Pressure Monitor – Advanced |

IN THE BOX

- G700 or G720 unit
- FlexGo™ bracket
- Tubing kit
- Power adapter
- Quick start guide
- Calibration certificate